

HRC FUSE BASE & CARRIERS ENCLOSED (TYPE MMF)



Description

Bakelite Moulded Fuse holders are available in different ratings i.e. 20 Amp. to 125 Amp. These are available in Bus Bar, Front & Rear Connection as per IS : 13703 Part 2 / Sec. 1 Type MMF Rated Voltage 415V, 50 Hz, AC.

HRC FUSE BASE OPEN TYPE BAKELITE / DMC MOULDED



Description

Bakelite Moulded Fuse Base are also available (Circlip & Spring Loaded) Type From 125Amp. to 630Amp. as per IS:13707 Part / Sec. 1 Type FBO Rated Voltage 415V, 50 Hz, AC.

INDUSTRIAL HOOTER / SOLID STATE BUZZERS / HEAVY DUTY FOOT SWITCH



Description

Hooter, (From 12V to 220V AC / DC) Audio output range 100 db to 120 db. also available in sheet metal & plastic housing Buzzer (From 12V to 220V AC / DC). Also available in multi tone version. Sound output 95 db to 110 db. panel cutout size 96x96mm & all range of Foot Switches


22.5 Ø PUSH BUTTON SWITCH



Description

Ø 22.5 mm Flush Button, Projecting Button available in Red, Green, Yellow, Blue & Black Selector Switch & Spring return Selector available in 2 position / 3 position Black colour.

22.5 Ø PUSH BUTTON SWITCH



Description

22.5 mm Mushroom Stayput press to lock & turn to reset / Mushroom spring return available in Red Colour. Key Selector Switch available in 2 / 3 lockable position & maintained position

22.5 Ø PUSH BUTTON SWITCH



Description

Ø 22.5 mm Luminous Twin Button Actuators, Luminous Flush Button (Spring Return) Actuators & Luminous 2 / 3 position selector Actuators & Mushroom Jumbo Button Actuators with 60mm dia head are available in Spring return press to lock & turn to reset

22.5 Ø CONTACT ELEMENT



Description

Ø 22.5 mm Contact Element 1 NO, 1 NC with Front & Rear Mounting / Contact Element 1 NO 1 NC with Front & Rear Mounting & Spare Bracket Carrier. TYPE - CFGV

22.5 Ø INDICATOR LIGHT

 <p>CFVILR Indicator Light</p>	 <p>CFVLDL-S Cluster LED Standard</p>	 <p>CFVLDLST Luminous Flush Button</p>	 <p>CFVLDL-BN Cluster LED (Barrel)</p>	<p>Description Ø 22.5 mm indicating Lights are available in glass filled Thermo-Plastic housing with polycarbonate lens in two version i.e. Barrel Type with Cluster LED & other standard type with Cluster LED / with bulb suitable for 24V, 110V / 220 / 230V AC / DC Supply with all colour</p>
---	--	---	---	---

PUSH BUTTON STATION / PENDENT PUSH BUTTON (CAST ALUMINIUM)

 <p>CFPS-229 Two Way Push Button station in cast aluminium</p>	 <p>CAPB-2292S Two Way Push Button station in cast aluminium</p>	 <p>CFPS-289 Ten Way Push Button station in cast aluminium</p>	 <p>CP-S3 Three Way Pendant in cast aluminium</p>	<p>Description Push Button Stations are available upto 4 ways and Pendant Push Button Stations available upto 20 way in cast aluminium housing & thermoplastic housing. All push Button Stations with IP55 / IP65 degree of protection.</p>
---	---	---	--	--

LIMIT SWITCH

 <p>CLS-100-0 Limit Switch Oil Tight</p>	 <p>CELS-100-1 Limit Switch Non Oil Tight</p>	 <p>CLS001-S Snap Action with Protective Cover</p>	 <p>CLS001-N Normal</p>	<p>Description Limit Switches with oil tight & non oil tight in Cast Aluminium housing with Contact Element, with Push Rod Normal Lever, Angular Lever, Open Execution Contact Element with Normal, Snap Action & Protective Cover in Bakelite Housing</p>
---	--	---	--	---

CAM OPERATED ROTARY SWITCH

 <p>CF-325 Ammeter Selector Switch (6A)</p>	 <p>CF-312 Voltmeter Selector Switch (6A)</p>	 <p>CF-195 ON-OFF Switch (16A)</p>	 <p>CF-001 ON-OFF Switch (6A)</p>	<p>Description Cam Operated Rotary Switches (From 6 Amp. to 63 Amp.) with 30°, 45° & 90° angle. Ammeter / Voltmeter Selector switch (6Amp. to 10Amp.) as per IS : 13947-1 / 3 / 5, 1993.</p>
--	--	---	--	---

CURRENT TRANSFORMER / SHUNTS

 <p>Current Transformer</p>	 <p>Current Transformer</p>	 <p>Shunt</p>	 <p>Shunt</p>	<p>Description Tape Wound C.T.'s CTR 1 Amp. to 5 Amp. also available 5VA, 10VA & 15VA Class C/M as per BS 3938-1965. Shunt Range of 50 mA to 1000 Amps. with drop range from 50 mV, 75mV, 100mV, 150 mV & 200mV.</p>
---	---	---	---	---

ANALOG METER / DIGITAL PANEL METER

 <p>CF-VM Volt Meter</p>	 <p>CF-AM Ammeter Meter</p>	 <p>CF-FQ Frequency Meter</p>	 <p>CF-DVM Digital Meter</p>	<p>Description Full Range of Volt Meter, Ammeter & Frequency Meter in Analog & Digital Type Size available 72 x 72mm, 96 x 96mm, 144 x 144mm AC/DC Supply conforming to BS 89 / 1994 & IS 1248-83 specifications.</p>
---	--	--	---	--

Authorised Stockist



Vaishno Switchgear (P) Ltd.

(An NS-EN ISO 14001:2004/ISO 14001:2004 Certified Company)

G-19, SECTOR-11, NOIDA-201301 (U. P.) INDIA

PH : +91(120) 4226777, 4226778

FAX: +91(120) 4335659

E-mail: sales@vaishno.co.in

website:www.indiamart.com/vaishno-sgr